



Emergency Telephones

100% Australian Owned

www.emergencytelephones.com.au

ETZD-27



Sales and Service:



Emergency Telephones

PO Box 606 Rockdale NSW 2216

Telephone: 02-9599-9555

Fax: 02-9599-9225

Email: sales@emergencytelephones.com.au


service@emergencytelephones.com.au

Emergency Telephones

100% Australian Owned

www.emergencytelephones.com.au

The Weatherproof phone will be designed to work on Railway, metro, tunnel, etc. Housed in cold rolled steel case with spring loaded door, it will offer protection against the outdoor environment, vandals resistance and rot resistance. The unit will meet all the latest European/UK standards for EMC and US FCC, telephony, waterproofing, and lightning protection together with offering the level of performance and reliability demanded in such an environment.



Main Product features

1. Cold rolled steel body, solid and temperature bearable
2. High durability, oil, acid, alkali resistance, conform to the standards of GJB - 773 and UL1332 requirements.
3. Highly integrated mainboard, using the most advanced industry-specific microcontroller made in ATMEL company.
4. The box with earthing device is completely isolated with internal electric circuit, and has certain electromagnetic shielding effect.
5. Conversation with clear loud voice, no feedback screaming.
6. Support hotline of exchange system.
7. Support the function of exterior line automatic lift.
8. Support conversation time limited.
9. Strong, thick and beautiful body with embed wall design.



- Standard and SMART Analogue and VoIP-SIP options available
- DTMF(Dual Tone Multi Frequency)
- Matching with most PABX,PBX and PAX systems.

Main PCB

1. Well treated PCB used inside the phone.
2. Robust screw terminals used for the connection of ringer, handset, line in, hookswitch.
3. Selectable 7 minute time out, to release the line if the handset is left off hook.
4. All connectors be greased in production.

Handset

1. Kirk electro dynamic transducer for both handset transmitter and receiver
2. Spring cable or armoured cable to attach the handset to the telephone main unit
3. Stainless steel cable to connect exchange.
4. Inductive coupler fitted for hearing aid compatibility.
5. Handset integrity wiring to enable exchange to check if the phone is still operational.

VOIC OVER IP- SIP (Version)

Connection type: RJ45 Socket inside sealed enclosure
Power supply: External 5V dc
Call set-up Protocol: Session Initiation Protocol(SIP)
Configuration: DHCP or STATIC IP address provisioning

Sales and Service:



Emergency Telephones

PO Box 606 Rockdale NSW 2216

Telephone: 02-9599-9555

Fax: 02-9599-9225

Email: sales@emergencytelephones.com.au

service@emergencytelephones.com.au




Emergency Telephones

100% Australian Owned

www.emergencytelephones.com.au


Telephone layout



TECHNICAL SPECIFICATION

1. It is suitable for automatic instruction amplification telephone system when feed voltage reaches to 33- 60V.
2. Environmental temperature: -30°C ~ 60°C
3. Relative humidity: 10% ~ 95%
4. Atmospheric pressure: 86 ~ 106Kpa
5. Environmental noise: $\leq 80\text{dB}$
6. Double audio dialing
7. Standard frequency: 697, 770, 852, 941Hz
8. Low frequency group: 697, 770, 852, 941Hz
9. High frequency group: 1209, 1336, 1477Hz
10. Frequency offset: $\leq \pm 1.5\%$
11. The signal level when the length of user's line is 3km:
12. Standard frequency: Low frequency group: -9dB
13. High frequency group: -7dB $\pm 3\text{dB}$
14. Level difference between high and low frequency of combined signal: $2\pm 1\text{dB}$
15. The total intermodulation distortion caused by harmonic is 20dB lower than wave level.
16. Call transmission index: (5Km) SLR ≤ 12 , RLR ≤ -1 , and STMR ≥ 10 , Input impedance: 600 Ω

Mounting bracket



Connection cable

Stainless steel connection cable to exchange.
Well treated keep waterproof.

Packing detail:



Unit size: 337*254*54mm, N.W: 2.3KG

1pcs in each inner CTN box, size: 439 *277 *191mm G.W: 3KG

4pcs in outer CTN box, size: 566 * 445 *420mm G.W: 13.3KG

Certification:

N30788



EMC: EN50121 (Railway application-
Electromagnetic Compatibility)
EN55022: emissions
EN55024: immunity

FCC
ITU-T Recommendations K21

Sales and Service:



Emergency Telephones

PO Box 606 Rockdale NSW 2216

Telephone: 02-9599-9555

Fax: 02-9599-9225

Email: sales@emergencytelephones.com.au

service@emergencytelephones.com.au